



Product Service

Attestation of Conformity

No. N8A 072237 0102 Rev. 03

Holder of Certificate: **Shenzhen INVT Electric Co., Ltd.**
INVT Guangming Technology Building, Songbai Road
Matian, Guangming District
518106 Shenzhen
PEOPLE'S REPUBLIC OF CHINA

Product: **Electronic frequency converter
(Frequency Inverter)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64105203041503

Date, 2022-06-20

(Frank Zhu)

Page 1 of 9

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 072237 0102 Rev. 03

Model(s):

GD300-132G-4, GD300-160P-4, GD300-160G-4,
 GD300-185P-4, GD300-185G-4, GD300-200P-4,
 GD300-200G-4, GD300-220P-4, GD300-220G-4,
 GD300-250P-4, GD300-250G-4, GD300-280P-4,
 GD300-280G-4, GD300-315P-4, GD300-315G-4,
 GD300-350P-4, GD300-350G-4, GD300-355G-4,
 GD300-400P-4, GD300-400G-4, GD300-450G-4,
 GD300-500G-4, GD200-132G-4, GD200-160P-4,
 GD200-132G/160P-4, GD200-160G-4, GD200-185P-4,
 GD200-160G/185P-4, GD200-185G-4, GD200-200P-4,
 GD200-185G/200P-4, GD200-200G-4, GD200-220P-4,
 GD200-200G/220P-4, GD200-220G-4, GD200-250P-4,
 GD200-220G/250P-4, GD200-250G-4, GD200-280P-4,
 GD200-250G/280P-4, GD200-280G-4, GD200-315P-4,
 GD200-280G/315P-4, GD200-315G-4, GD200-350P-4,
 GD200-315G/350P-4, GD200-350G-4, GD200-400P-4,
 GD200-350G/400P-4, GD200-400G-4, GD200-500G-4,
 GD200A-132G-4, GD200A-160P-4, GD200A-160G-4,
 GD200A-185P-4, GD200A-185G-4, GD200A-200P-4,
 GD200A-200G-4, GD200A-220P-4, GD200A-220G-4,
 GD200A-250P-4, GD200A-250G-4, GD200A-280P-4,
 GD200A-280G-4, GD200A-315P-4, GD200A-315G-4,
 GD200A-350P-4, GD200A-350G-4, GD200A-400P-4,
 GD200A-355G-4, GD200A-400G-4, GD200A-450G-4,
 GD200A-500G-4, GD200A-132G/160P-4,
 GD200A-160G/185P-4, GD200A-185G/200P-4,
 GD200A-200G/220P-4, GD200A-220G/250P-4,
 GD200A-250G/280P-4, GD200A-280G/315P-4,
 GD200A-315G/355P-4, GD200A-355G/400P-4,
 GD350A-132G/160P-4, GD350A-160G/185P-4,
 GD350A-185G/200P-4, GD350A-200G/220P-4,
 GD350A-220G/250P-4, GD350A-250G/280P-4,
 GD350A-280G/315P-4, GD350A-315G/355P-4,
 GD350A-355G/400P-4, GD350A-400G/450P-4,
 GD350A-450G/500P-4, GD350A-500G-4

Page 2 of 9

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 072237 0102 Rev. 03

Brand: INVT



Parameters:

Rated Input:	See below pages
Rated Output:	See below pages
Installation:	BDM
Protection Class:	I
Degree of Protection:	IP 20
Construction:	Built-in

Remarks:

- When installing the equipment, all requirements of the mentioned standard must be fulfilled and it should be suitably installed in closed electrical operation area, and fire/mechanical protection enclosure shall be provided.
- Maximum operating temperature is 40°C.
- The input and output circuits were considered as DVC C circuits and signal circuit was considered as DVC A circuit.
- TN-S, TN-C, TN-C-S and TT (not corner earthed) power systems were evaluated.
- The frequency inverter has no overcurrent protective device. For safe operation, a suitable external circuit breaker must be employed before installation.

Tested according to: EN 61800-5-1:2007/A11:2021

Page 3 of 9

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 072237 0102 Rev. 03

Parameters:

Model No.	Rated Input	Rated Output
GD300-132G-4	3 PH, 380-480V, 47-63Hz, 265.0A	3 PH, 0-Uinput, 0-400Hz, 260.0A, 132.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 265.0A	
GD300-160P-4	3 PH, 380-480V, 47-63Hz, 310.0A	3 PH, 0-Uinput, 0-400Hz, 305.0A, 160.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 310.0A	
GD300-160G-4	3 PH, 380-480V, 47-63Hz, 310.0A	3 PH, 0-Uinput, 0-400Hz, 305.0A, 160.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 310.0A	
GD300-185P-4	3 PH, 380-480V, 47-63Hz, 345.0A	3 PH, 0-Uinput, 0-400Hz, 340.0A, 185.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 345.0A	
GD300-185G-4	3 PH, 380-480V, 47-63Hz, 345.0A	3 PH, 0-Uinput, 0-400Hz, 340.0A, 185.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 345.0A	
GD300-200P-4	3 PH, 380-480V, 47-63Hz, 385.0A	3 PH, 0-Uinput, 0-400Hz, 380.0A, 200.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 385.0A	
GD300-200G-4	3 PH, 380-480V, 47-63Hz, 385.0A	3 PH, 0-Uinput, 0-400Hz, 380.0A, 200.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 385.0A	
GD300-220P-4	3 PH, 380-480V, 47-63Hz, 430.0A	3 PH, 0-Uinput, 0-400Hz, 425.0A, 220.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 430.0A	
GD300-220G-4	3 PH, 380-480V, 47-63Hz, 430.0A	3 PH, 0-Uinput, 0-400Hz, 425.0A, 220.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 430.0A	
GD300-250P-4	3 PH, 380-480V, 47-63Hz, 485.0A	3 PH, 0-Uinput, 0-400Hz, 480.0A, 250.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 485.0A	
GD300-250G-4	3 PH, 380-480V, 47-63Hz, 485.0A	3 PH, 0-Uinput, 0-400Hz, 480.0A, 250.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 485.0A	
GD300-280P-4	3 PH, 380-480V, 47-63Hz, 545.0A	3 PH, 0-Uinput, 0-400Hz, 530.0A, 280.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 545.0A	
GD300-280G-4	3 PH, 380-480V, 47-63Hz, 545.0A	3 PH, 0-Uinput, 0-400Hz, 530.0A, 280.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 545.0A	
GD300-315P-4	3 PH, 380-480V, 47-63Hz, 610.0A	3 PH, 0-Uinput, 0-400Hz, 600.0A, 315.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 610.0A	
GD300-315G-4	3 PH, 380-480V, 47-63Hz, 610.0A	3 PH, 0-Uinput, 0-400Hz, 600.0A, 315.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 610.0A	
GD300-350P-4	3 PH, 380-480V, 47-63Hz, 625.0A	3 PH, 0-Uinput, 0-400Hz, 650.0A, 350.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625.0A	
GD300-350G-4	3 PH, 380-480V, 47-63Hz, 625.0A	3 PH, 0-Uinput, 0-400Hz, 650.0A, 350.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625.0A	
GD300-355G-4	3 PH, 380-480V, 47-63Hz, 625.0A	3 PH, 0-Uinput, 0-400Hz, 650.0A, 355.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625.0A	
GD300-400P-4	3 PH, 380-480V, 47-63Hz, 715.0A	3 PH, 0-Uinput, 0-400Hz, 720.0A, 400.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 715.0A	
GD300-400G-4	3 PH, 380-480V, 47-63Hz, 715.0A	3 PH, 0-Uinput, 0-400Hz, 820.0A, 400.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 715.0A	
GD300-450G-4	3 PH, 380-480V, 47-63Hz, 840.0A	3 PH, 0-Uinput, 0-400Hz, 820.0A, 450.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 840.0A	
GD300-500G-4	3 PH, 380-480V, 47-63Hz, 890.0A	3 PH, 0-Uinput, 0-400Hz, 860.0A, 500.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 890.0A	



Attestation of Conformity

No. N8A 072237 0102 Rev. 03

Model No.	Rated Input	Rated Output
GD200-132G-4	3 PH, 380-480V, 47-63Hz, 265.0A	3 PH, 0-Uinput, 0-400Hz, 260.0A, 132.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 265.0A	
GD200-160P-4	3 PH, 380-480V, 47-63Hz, 310.0A	3 PH, 0-Uinput, 0-400Hz, 305.0A, 160.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 310.0A	
GD200-132G/160P-4	3 PH, 380-480V, 47-63Hz, 265.0/310.0A	3 PH, 0-Uinput, 0-400Hz, 260.0/305.0A, 132.0/160.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 265.0/310.0A	
GD200-160G-4	3 PH, 380-480V, 47-63Hz, 310.0A	3 PH, 0-Uinput, 0-400Hz, 305.0A, 160.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 310.0A	
GD200-185P-4	3 PH, 380-480V, 47-63Hz, 345.0A	3 PH, 0-Uinput, 0-400Hz, 340.0A, 185.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 345.0A	
GD200-160G/185P-4	3 PH, 380-480V, 47-63Hz, 310.0/345.0A	3 PH, 0-Uinput, 0-400Hz, 305.0/340.0A, 160.0/185.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 310.0/345.0A	
GD200-185G-4	3 PH, 380-480V, 47-63Hz, 345.0A	3 PH, 0-Uinput, 0-400Hz, 340.0A, 185.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 345.0A	
GD200-200P-4	3 PH, 380-480V, 47-63Hz, 385.0A	3 PH, 0-Uinput, 0-400Hz, 380.0A, 200.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 385.0A	
GD200-185G/200P-4	3 PH, 380-480V, 47-63Hz, 345.0/385.0A	3 PH, 0-Uinput, 0-400Hz, 340.0/380.0A, 185.0/200.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 345.0/385.0A	
GD200-200G-4	3 PH, 380-480V, 47-63Hz, 385.0A	3 PH, 0-Uinput, 0-400Hz, 380.0A, 200.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 385.0A	
GD200-220P-4	3 PH, 380-480V, 47-63Hz, 430.0A	3 PH, 0-Uinput, 0-400Hz, 425.0A, 220.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 430.0A	
GD200-200G/220P-4	3 PH, 380-480V, 47-63Hz, 385.0/430.0A	3 PH, 0-Uinput, 0-400Hz, 380.0/425.0A, 200.0/220.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 385.0/430.0A	
GD200-220G-4	3 PH, 380-480V, 47-63Hz, 430.0A	3 PH, 0-Uinput, 0-400Hz, 425.0A, 220.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 430.0A	
GD200-250P-4	3 PH, 380-480V, 47-63Hz, 485.0A	3 PH, 0-Uinput, 0-400Hz, 480.0A, 250.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 485.0A	
GD200-220G/250P-4	3 PH, 380-480V, 47-63Hz, 430.0/485.0A	3 PH, 0-Uinput, 0-400Hz, 425.0/480.0A, 220.0/250.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 430.0/485.0A	
GD200-250G-4	3 PH, 380-480V, 47-63Hz, 485.0A	3 PH, 0-Uinput, 0-400Hz, 480.0A, 250.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 485.0A	
GD200-280P-4	3 PH, 380-480V, 47-63Hz, 545.0A	3 PH, 0-Uinput, 0-400Hz, 530.0A, 280.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 545.0A	



Product Service

Attestation of Conformity

No. N8A 072237 0102 Rev. 03

GD200-250G/280P-4	3 PH, 380-480V, 47-63Hz, 485.0/545.0A	3 PH, 0-Uinput, 0-400Hz, 480.0/530.0A, 250.0/280.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 485.0/545.0A	
GD200-280G-4	3 PH, 380-480V, 47-63Hz, 545.0A	3 PH, 0-Uinput, 0-400Hz, 530.0A, 280.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 545.0A	
GD200-315P-4	3 PH, 380-480V, 47-63Hz, 610.0A	3 PH, 0-Uinput, 0-400Hz, 600.0A, 315.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 610.0A	
GD200-280G/315P-4	3 PH, 380-480V, 47-63Hz, 545.0/610.0A	3 PH, 0-Uinput, 0-400Hz, 530.0/600.0A, 280.0/315.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 545.0/610.0A	
GD200-315G-4	3 PH, 380-480V, 47-63Hz, 610.0A	3 PH, 0-Uinput, 0-400Hz, 600.0A, 315.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 610.0A	
GD200-350P-4	3 PH, 380-480V, 47-63Hz, 625.0A	3 PH, 0-Uinput, 0-400Hz, 650.0A, 350.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625.0A	
GD200-315G/350P-4	3 PH, 380-480V, 47-63Hz, 610.0/625.0A	3 PH, 0-Uinput, 0-400Hz, 600.0/650.0A, 315.0/350.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 610.0/625.0A	
GD200-350G-4	3 PH, 380-480V, 47-63Hz, 625.0A	3 PH, 0-Uinput, 0-400Hz, 650.0A, 350.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625.0A	
GD200-400P-4	3 PH, 380-480V, 47-63Hz, 715.0A	3 PH, 0-Uinput, 0-400Hz, 720.0A, 400.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 715.0A	
GD200-350G/400P-4	3 PH, 380-480V, 47-63Hz, 625.0/715.0A	3 PH, 0-Uinput, 0-400Hz, 650.0/720.0A, 350.0/400.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625.0/715.0A	
GD200-400G-4	3 PH, 380-480V, 47-63Hz, 715.0A	3 PH, 0-Uinput, 0-400Hz, 720.0A, 400.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 715.0A	
GD200-500G-4	3 PH, 380-480V, 47-63Hz, 890.0A	3 PH, 0-Uinput, 0-400Hz, 860.0A, 500.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 890.0A	

Page 6 of 9

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 072237 0102 Rev. 03

Model No.	Rated Input	Rated Output
GD200A-132G-4	3 PH, 380-480V, 47-63Hz, 265.0A	3 PH, 0-Uinput, 0-400Hz, 260.0A, 132.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 265.0A	
GD200A-160P-4	3 PH, 380-480V, 47-63Hz, 310.0A	3 PH, 0-Uinput, 0-400Hz, 305.0A, 160.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 310.0A	
GD200A-132G/160P-4	3 PH, 380-480V, 47-63Hz, 265/310A	3 PH, 0-Uinput, 0-400Hz, 260/305A, 132/160 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 265/310A	
GD200A-160G-4	3 PH, 380-480V, 47-63Hz, 310.0A	3 PH, 0-Uinput, 0-400Hz, 305.0A, 160.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 310.0A	
GD200A-185P-4	3 PH, 380-480V, 47-63Hz, 345.0A	3 PH, 0-Uinput, 0-400Hz, 340.0A, 185.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 345.0A	
GD200A-160G/185P-4	3 PH, 380-480V, 47-63Hz, 310/345A	3 PH, 0-Uinput, 0-400Hz, 305/340A, 160/185 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 310/345A	
GD200A-185G-4	3 PH, 380-480V, 47-63Hz, 345.0A	3 PH, 0-Uinput, 0-400Hz, 340.0A, 185.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 345.0A	
GD200A-200P-4	3 PH, 380-480V, 47-63Hz, 385.0A	3 PH, 0-Uinput, 0-400Hz, 380.0A, 200.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 385.0A	
GD200A-185G/200P-4	3 PH, 380-480V, 47-63Hz, 345/385A	3 PH, 0-Uinput, 0-400Hz, 340/380A, 185/200 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 345/385A	
GD200A-200G-4	3 PH, 380-480V, 47-63Hz, 385.0A	3 PH, 0-Uinput, 0-400Hz, 380.0A, 200.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 385.0A	
GD200A-220P-4	3 PH, 380-480V, 47-63Hz, 430.0A	3 PH, 0-Uinput, 0-400Hz, 425.0A, 220.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 430.0A	
GD200A-200G/220P-4	3 PH, 380-480V, 47-63Hz, 385/430A	3 PH, 0-Uinput, 0-400Hz, 380/425A, 200/220 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 385/430A	
GD200A-220G-4	3 PH, 380-480V, 47-63Hz, 430.0A	3 PH, 0-Uinput, 0-400Hz, 425.0A, 220.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 430.0A	
GD200A-250P-4	3 PH, 380-480V, 47-63Hz, 485.0A	3 PH, 0-Uinput, 0-400Hz, 480.0A, 250.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 485.0A	
GD200A-220G/250P-4	3 PH, 380-480V, 47-63Hz, 430/485A	3 PH, 0-Uinput, 0-400Hz, 425/480A, 220/250 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 430/485A	
GD200A-250G-4	3 PH, 380-480V, 47-63Hz, 485.0A	3 PH, 0-Uinput, 0-400Hz, 480.0A, 250.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 485.0A	
GD200A-280P-4	3 PH, 380-480V, 47-63Hz, 545.0A	3 PH, 0-Uinput, 0-400Hz, 530.0A, 280.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 545.0A	
GD200A-250G/280P-4	3 PH, 380-480V, 47-63Hz, 485/545A	3 PH, 0-Uinput, 0-400Hz, 480/530A, 250/280 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 485/545A	
GD200A-280G-4	3 PH, 380-480V, 47-63Hz, 545.0A	3 PH, 0-Uinput, 0-400Hz, 530.0A, 280.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 545.0A	
GD200A-315P-4	3 PH, 380-480V, 47-63Hz, 610.0A	3 PH, 0-Uinput, 0-400Hz, 600.0A, 315.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 610.0A	



Attestation of Conformity

No. N8A 072237 0102 Rev. 03

GD200A-280G/315P-4	3 PH, 380-480V, 47-63Hz, 545/610A	3 PH, 0-Uinput, 0-400Hz, 530/600A, 280/315 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 545/610A	
GD200A-315G-4	3 PH, 380-480V, 47-63Hz, 610.0A	3 PH, 0-Uinput, 0-400Hz, 600.0A, 315.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 610.0A	
GD200A-350P-4	3 PH, 380-480V, 47-63Hz, 625.0A	3 PH, 0-Uinput, 0-400Hz, 650.0A, 350.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625.0A	
GD200A-315G/350P-4	3 PH, 380-480V, 47-63Hz, 610/625A	3 PH, 0-Uinput, 0-400Hz, 600/650A, 315/355 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 610/625A	
GD200A-350G-4	3 PH, 380-480V, 47-63Hz, 625.0A	3 PH, 0-Uinput, 0-400Hz, 650.0A, 350.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625.0A	
GD200A-355G-4	3 PH, 380-480V, 47-63Hz, 625.0A	3 PH, 0-Uinput, 0-400Hz, 650.0A, 355.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625.0A	
GD200A-400P-4	3 PH, 380-480V, 47-63Hz, 715.0A	3 PH, 0-Uinput, 0-400Hz, 720.0A, 400.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 715.0A	
GD200A-355G/400P-4	3 PH, 380-480V, 47-63Hz, 625/715A	3 PH, 0-Uinput, 0-400Hz, 650/720A, 355/400 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625/715A	
GD200A-400G-4	3 PH, 380-480V, 47-63Hz, 715.0A	3 PH, 0-Uinput, 0-400Hz, 720.0A, 400.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 715.0A	
GD200A-450G-4	3 PH, 380-480V, 47-63Hz, 840.0A	3 PH, 0-Uinput, 0-400Hz, 820.0A, 450.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 840.0A	
GD200A-500G-4	3 PH, 380-480V, 47-63Hz, 890.0A	3 PH, 0-Uinput, 0-400Hz, 860.0A, 500.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 890.0A	



Attestation of Conformity

No. N8A 072237 0102 Rev. 03

Model No.	Rated Input	Rated Output
GD350A-132G/160P-4	3 PH, 380-480V, 47-63Hz, 265/310A	3 PH, 0-Uinput, 0-400Hz, 260/305A, 132/160 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 265/310A	
GD350A-160G/185P-4	3 PH, 380-480V, 47-63Hz, 310/345A	3 PH, 0-Uinput, 0-400Hz, 305/340A, 160/185 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 310/345A	
GD350A-185G/200P-4	3 PH, 380-480V, 47-63Hz, 345/385A	3 PH, 0-Uinput, 0-400Hz, 340/380A, 185/200 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 345/385A	
GD350A-200G/220P-4	3 PH, 380-480V, 47-63Hz, 385/430A	3 PH, 0-Uinput, 0-400Hz, 380/425A, 200/220 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 385/430A	
GD350A-220G/250P-4	3 PH, 380-480V, 47-63Hz, 430/460A	3 PH, 0-Uinput, 0-400Hz, 425/480A, 220/250 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 430/460A	
GD350A-250G/280P-4	3 PH, 380-480V, 47-63Hz, 460/500A	3 PH, 0-Uinput, 0-400Hz, 480/530A, 250/280 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 460/500A	
GD350A-280G/315P-4	3 PH, 380-480V, 47-63Hz, 500/580A	3 PH, 0-Uinput, 0-400Hz, 530/600A, 280/315 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 500/580A	
GD350A-315G/355P-4	3 PH, 380-480V, 47-63Hz, 580/625A	3 PH, 0-Uinput, 0-400Hz, 600/650A, 315/355 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 580/625A	
GD350A-355G/400P-4	3 PH, 380-480V, 47-63Hz, 625/715A	3 PH, 0-Uinput, 0-400Hz, 650/720A, 355/400 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 625/715A	
GD350A-400G/450P-4	3 PH, 380-480V, 47-63Hz, 715/840A	3 PH, 0-Uinput, 0-400Hz, 720/820A, 400/450 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 715/840A	
GD350A-450G/500P-4	3 PH, 380-480V, 47-63Hz, 840/890A	3 PH, 0-Uinput, 0-400Hz, 820/860A, 450/500 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 840/890A	
GD350A-500G-4	3 PH, 380-480V, 47-63Hz, 890.0A	3 PH, 0-Uinput, 0-400Hz, 860.0A, 500.0 kW
	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 890.0A	