



Product Service

Attestation of Conformity

No. N8A 072237 0098 Rev. 03

Holder of Certificate: **Shenzhen INVT Electric Co., Ltd.**
INVT Guangming Technology Building, Songbai Road
Matian, Guangming District
518106 Shenzhen
PEOPLE'S REPUBLIC OF CHINA

Product: **Electronic frequency converter
(Frequency Inverter)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64105203041302

Date, 2022-06-20

(Frank Zhu)

Page 1 of 10

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 072237 0098 Rev. 03

Model(s):

GD300-1R5G-4, GD300-2R2G-4, GD300-004G-4,
 GD300-5R5P-4, GD300-5R5G-4, GD300-7R5P-4,
 GD300-7R5G-4, GD300-011P-4, GD300-011G-4,
 GD300-015P-4, GD300-015G-4, GD300-018P-4,
 GD300-018G-4, GD300-022P-4, GD200-1R5G-4,
 GD200-2R2G-4, GD200-004G-4, GD200-5R5P-4,
 GD200-004G/5R5P-4, GD200-5R5G-4, GD200-7R5P-4,
 GD200-5R5G/7R5P-4, GD200-7R5G-4, GD200-011P-4,
 GD200-7R5G/011P-4, GD200-011G-4, GD200-015P-4,
 GD200-011G/015P-4, GD200-015G-4, GD200-018P-4,
 GD200-015G/018P-4, GD200-018G-4, GD200-022P-4,
 GD200-018G/022P-4, GD35-004G-4-A1, GD35-004G-4-B1,
 GD35-004G-4-C1, GD35-004G-4-D1, GD35-004G-4-H1,
 GD35-5R5G-4-A1, GD35-5R5G-4-B1, GD35-5R5G-4-C1,
 GD35-5R5G-4-D1, GD35-5R5G-4-H1, GD35-7R5G-4-A1,
 GD35-7R5G-4-B1, GD35-7R5G-4-C1, GD35-7R5G-4-D1,
 GD35-7R5G-4-H1, GD35-011G-4-A1, GD35-011G-4-B1,
 GD35-011G-4-C1, GD35-011G-4-D1, GD35-011G-4-H1,
 GD35-015G-4-A1, GD35-015G-4-B1, GD35-015G-4-C1,
 GD35-015G-4-D1, GD35-015G-4-H1, GD200A-0R7G-4,
 GD200A-1R5G-4, GD200A-2R2G-4, GD200A-004G-4,
 GD200A-5R5P-4, GD200A-004G/5R5P-4,
 GD200A-5R5G-4, GD200A-7R5P-4,
 GD200A-5R5G/7R5P-4, GD200A-7R5G-4,
 GD200A-011P-4, GD200A-7R5G/011P-4, GD200A-011G-4,
 GD200A-015P-4, GD200A-011G/015P-4, GD200A-015G-4,
 GD200A-018P-4, GD200A-015G/018P-4, GD200A-018G-4,
 GD200A-022P-4, GD200A-018G/022P-4,
 GD350A-1R5G/2R2P-4, GD350A-2R2G/003P-4,
 GD350A-004G/5R5P-4, GD350A-5R5G/7R5P-4,
 GD350A-7R5G/011P-4, GD350A-011G/015P-4,
 GD350A-015G/018P-4

Brand:

INVT



Page 2 of 10

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 072237 0098 Rev. 03

Parameters:

Rated input:	See below pages
Rated output:	See below pages
Installation:	BDM
Protection Class:	I
Degree of Protection:	IP 20
Rated Operating time:	Continuous
Construction:	Built-in

Remark:

- When installing the equipment, all requirements of the mentioned standard must be fulfilled and it should be suitably installed in closed electrical operation area, and fire/mechanical protection enclosure shall be provided.
- The maximum operating temperature is 40°C
- The input and output circuits were considered as DVC C circuits and signal circuit was considered as DVC A circuit.
- TN-S, TN-C, TN-C-S, TT (not corner earthed) power systems were evaluated.
- The equipment has no overcurrent protective device. For safety operation, a suitable external circuit breaker must be employed before installation.

**Tested
according to:**

EN 61800-5-1:2007/A11:2021

Page 3 of 10

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 072237 0098 Rev. 03

Parameters:

Model No.	Rated input	Rated output*	Size (mm)	
GD300-1R5G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 5.0A	3 PH, 0V-Uinput, 0-400Hz, 3.7A, 1.5 kW	A:193x126x174.5	
	3 PH, 380V-480V, 47-63Hz, 5.0A			
GD300-2R2G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 5.8A	3 PH, 0V-Uinput, 0-400Hz, 5.0A, 2.2 kW		
	3 PH, 380V-480V, 47-63Hz, 5.8A			
GD300-004G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 13.5A	3 PH, 0V-Uinput, 0-400Hz, 9.5A, 4.0 kW	B:263x146x181	
	3 PH, 380V-480V, 47-63Hz, 13.5A			
GD300-5R5P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 19.5A	3 PH, 0V-Uinput, 0-400Hz, 14.0A, 5.5 kW		
	3 PH, 380V-480V, 47-63Hz, 19.5A			
GD300-5R5G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 19.5A	3 PH, 0V-Uinput, 0-400Hz, 14.0A, 5.5 kW		
	3 PH, 380V-480V, 47-63Hz, 19.5A			
GD300-7R5P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 25.0A	3 PH, 0V-Uinput, 0-400Hz, 18.5A, 7.5 kW	C:331.5x170.0x216.2	
	3 PH, 380V-480V, 47-63Hz, 25.0A			
GD300-7R5G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 25.0A	3 PH, 0V-Uinput, 0-400Hz, 18.5A, 7.5 kW		
	3 PH, 380V-480V, 47-63Hz, 25.0A			
GD300-011P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 32.0A	3 PH, 0V-Uinput, 0-400Hz, 25.0A, 11.0 kW		
	3 PH, 380V-480V, 47-63Hz, 32.0A			
GD300-011G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 32.0A	3 PH, 0V-Uinput, 0-400Hz, 25.0A, 11.0 kW		
	3 PH, 380V-480V, 47-63Hz, 32.0A			
GD300-015P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 40.0A	3 PH, 0V-Uinput, 0-400Hz, 32.0A, 15.0 kW		D:342x230x216
	3 PH, 380V-480V, 47-63Hz, 40.0A			
GD300-015G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 40.0A	3 PH, 0V-Uinput, 0-400Hz, 32.0A, 15.0 kW		
	3 PH, 380V-480V, 47-63Hz, 40.0A			
GD300-018P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 47A	3 PH, 0V-Uinput, 0-400Hz, 38.0A, 18.5 kW		
	3 PH, 380V-480V, 47-63Hz, 47A			
GD300-018G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 47A	3 PH, 0V-Uinput, 0-400Hz, 38.0A, 18.5 kW		
	3 PH, 380V-480V, 47-63Hz, 47A			
GD300-022P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 56A	3 PH, 0V-Uinput, 0-400Hz, 45.0A, 22 kW		
	3 PH, 380V-480V, 47-63Hz, 56A			

*Remark: Uinput means Rated Input Voltage



Attestation of Conformity

No. N8A 072237 0098 Rev. 03

Model No.	Rated input	Rated output*	Size (mm)
GD200-1R5G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 5.0A	3 PH, 0V-Uinput, 0-400Hz, 3.7A, 1.5 kW	A:193x126x174.5
	3 PH, 380V-480V, 47-63Hz, 5.0A		
GD200-2R2G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 5.8A	3 PH, 0V-Uinput, 0-400Hz, 5.0A, 2.2 kW	
	3 PH, 380V-480V, 47-63Hz, 5.8A		
GD200-004G-4	3 PH, 380V(-15%)-400V(+10%), 47-63Hz, 13.5A	3 PH, 0V-Uinput, 0-400Hz, 9.5A, 4.0 kW	B:263x146x181
	3 PH, 380V-480V, 47-63Hz, 13.5A		
GD200-5R5P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 19.5A	3 PH, 0V-Uinput, 0-400Hz, 14.0A, 5.5 kW	
	3 PH, 380V-480V, 47-63Hz, 19.5A		
GD200-004G/5R5P-4	3 PH, 380V(-15%)-400V(+10%), 47-63Hz, 13.5/19.5A	3 PH, 0V-Uinput, 0-400Hz, 9.5/14.0A, 4.0/5.5 kW	
	3 PH, 380V-480V, 47-63Hz, 13.5/19.5A		
GD200-5R5G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 19.5A	3 PH, 0V-Uinput, 0-400Hz, 14.0A, 5.5 kW	
	3 PH, 380V-480V, 47-63Hz, 19.5A		
GD200-7R5P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 25.0A	3 PH, 0V-Uinput, 0-400Hz, 18.5A, 7.5 kW	
	3 PH, 380V-480V, 47-63Hz, 25.0A		
GD200-5R5G/7R5P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 19.5/25.0A	3 PH, 0V-Uinput, 0-400Hz, 14.0/18.5A, 5.5/7.5 kW	
	3 PH, 380V-480V, 47-63Hz, 19.5/25.0A		
GD200-7R5G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 25.0A	3 PH, 0V-Uinput, 0-400Hz, 18.5A, 7.5 kW	C:331.5x170.0x216.2
	3 PH, 380V-480V, 47-63Hz, 25.0A		
GD200-011P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 32.0A	3 PH, 0V-Uinput, 0-400Hz, 25.0A, 11.0 kW	
	3 PH, 380V-480V, 47-63Hz, 32.0A		
GD200-7R5G/011P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 25.0/32.0A	3 PH, 0V-Uinput, 0-400Hz, 18.5/25.0A, 7.5/11.0 kW	
	3 PH, 380V-480V, 47-63Hz, 25.0/32.0A		
GD200-011G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 32.0A	3 PH, 0V-Uinput, 0-400Hz, 25.0A, 11.0 kW	
	3 PH, 380V-480V, 47-63Hz, 32.0A		
GD200-015P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 40.0A	3 PH, 0V-Uinput, 0-400Hz, 32.0A, 15.0 kW	
	3 PH, 380V-480V, 47-63Hz, 40.0A		



Attestation of Conformity

No. N8A 072237 0098 Rev. 03

GD200-011G/015P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 32.0/40.0A	3 PH, 0V-Uinput, 0-400Hz, 25.0/32.0A, 11.0/15.0 kW	D:342x230x216
	3 PH, 380V-480V, 47-63Hz, 32.0/40.0A		
GD200-015G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 40.0A	3 PH, 0V-Uinput, 0-400Hz, 32.0A, 15.0 kW	
	3 PH, 380V-480V, 47-63Hz, 40.0A		
GD200-018P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 47A	3 PH, 0V-Uinput, 0-400Hz, 38.0A, 18.5 kW	
	3 PH, 380V-480V, 47-63Hz, 47A		
GD200-015G/018P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 40.0/47A	3 PH, 0V-Uinput, 0-400Hz, 32.0/38.0A, 15.0/18.5 kW	
	3 PH, 380V-480V, 47-63Hz, 40.0/47A		
GD200-018G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 47A	3 PH, 0V-Uinput, 0-400Hz, 38.0A, 18.5 kW	
	3 PH, 380V-480V, 47-63Hz, 47A		
GD200-022P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 56A	3 PH, 0V-Uinput, 0-400Hz, 45.0A, 22 kW	
	3 PH, 380V-480V, 47-63Hz, 56A		
GD200-018G/022P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 47/56A	3 PH, 0V-Uinput, 0-400Hz, 38.0/45.0A, 18.5/22 kW	
	3 PH, 380V-480V, 47-63Hz, 47/56A		
*Remark: Uinput means Rated Input Voltage			



Product Service

Attestation of Conformity

No. N8A 072237 0098 Rev. 03

Model No.	Rated Input	Rated output*	Size (mm)	
GD35-004G-4-A1, GD35-004G-4-B1, GD35-004G-4-C1, GD35-004G-4-D1, GD35-004G-4-H1	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,13.5A	3 PH, 0V-Uinput, 0-400Hz, 9.5A, 4.0 kW	B:263x146x181	
	3 PH, 380V-480V, 47-63Hz, 13.5A			
GD35-5R5G-4-A1, GD35-5R5G-4-B1, GD35-5R5G-4-C1, GD35-5R5G-4-D1, GD35-5R5G-4-H1	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,19.5A	3 PH, 0V-Uinput, 0-400Hz, 14.0A, 5.5 kW		
	3 PH, 380V-480V, 47-63Hz, 19.5A			
GD35-7R5G-4-A1, GD35-7R5G-4-B1, GD35-7R5G-4-C1, GD35-7R5G-4-D1, GD35-7R5G-4-H1	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 25.0A	3 PH, 0V-Uinput, 0-400Hz, 18.5A, 7.5 kW		C:331.5x170.0x216.2
	3 PH, 380V-480V, 47-63Hz, 25.0A			
GD35-011G-4-A1, GD35-011G-4-B1, GD35-011G-4-C1, GD35-011G-4-D1, GD35-011G-4-H1	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 32.0A	3 PH, 0V-Uinput, 0-400Hz, 25.0A, 11.0 kW		
	3 PH, 380V-480V, 47-63Hz, 32.0A			
GD35-015G-4-A1, GD35-015G-4-B1, GD35-015G-4-C1, GD35-015G-4-D1, GD35-015G-4-H1	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 40.0A	3 PH, 0V-Uinput, 0-400Hz, 32.0A, 15.0 kW	D:342x230x216	
	3 PH, 380V-480V, 47-63Hz, 40.0A			

*Remark: Uinput means Rated Input Voltage



Attestation of Conformity

No. N8A 072237 0098 Rev. 03

Model No.	Rated Input	Rated Output	Size (mm)	
GD200A-0R7G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 3.4A	3 PH, 0V-Uinput, 0-400Hz, 2.5A, 0.75 kW	E:186x126x155	
	3 PH, 380V-480V, 47-63Hz, 3.4A			
GD200A-1R5G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 5.0A	3 PH, 0V-Uinput, 0-400Hz, 3.7A, 1.5 kW		
	3 PH, 380V-480V, 47-63Hz, 5.0A			
GD200A-2R2G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 5.8A	3 PH, 0V-Uinput, 0-400Hz, 5.0A, 2.2 kW		
	3 PH, 380V-480V, 47-63Hz, 5.8A			
GD200A-004G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 13.5A	3 PH, 0V-Uinput, 0-400Hz, 9.5A, 4.0 kW		F:256x146x-171
	3 PH, 380V-480V, 47-63Hz, 13.5A			
GD200A-5R5P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 19.5A	3 PH, 0V-Uinput, 0-400Hz, 14.0A, 5.5 kW		
	3 PH, 380V-480V, 47-63Hz, 19.5A			
GD200A-004G/5R5P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 13.5/19.5A	3 PH, 0V-Uinput, 0-400Hz, 9.5/14.0A, 4.0/5.5 kW		
	3 PH, 380V-480V, 47-63Hz, 13.5/19.5A			
GD200A-5R5G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 19.5A	3 PH, 0V-Uinput, 0-400Hz, 14.0A, 5.5 kW		
	3 PH, 380V-480V, 47-63Hz, 19.5A			
GD200A -7R5P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 25.0A	3 PH, 0V-Uinput, 0-400Hz, 18.5A, 7.5 kW		
	3 PH, 380V-480V, 47-63Hz, 25.0A			
GD200A-5R5G/7R5P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 19.5/25.0A	3 PH, 0V-Uinput, 0-400Hz, 14.0/18.5A, 5.5/7.5 kW		
	3 PH, 380V-480V, 47-63Hz, 19.5/25.0A			
GD200A-7R5G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 25.0A	3 PH, 0V-Uinput, 0-400Hz, 18.5A, 7.5 kW	G:320x170.0x199.6	
	3 PH, 380V-480V, 47-63Hz, 25.0A			
GD200A-011P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 32.0A	3 PH, 0V-Uinput, 0-400Hz, 25.0A, 11.0 kW		
	3 PH, 380V-480V, 47-63Hz, 32.0A			
GD200A-7R5G/011P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 25.0/32.0A	3 PH, 0V-Uinput, 0-400Hz, 18.5/25.0A, 7.5/11.0 kW		
	3 PH, 380V-480V, 47-63Hz, 25.0/32.0A			
GD200A-011G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 32.0A	3 PH, 0V-Uinput, 0-400Hz, 25.0A, 11.0 kW		
	3 PH, 380V-480V, 47-63Hz, 32.0A			
GD200A-015P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 40.0A	3 PH, 0V-Uinput, 0-400Hz, 32.0A,		

Page 8 of 10

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 072237 0098 Rev. 03

	3 PH, 380V-480V, 47-63Hz, 40.0A	15.0 kW	
GD200A-011G/015P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 32.0/40.0A	3 PH, 0V-Uinput, 0-400Hz, 25.0/32.0A, 11.0/15.0kW	H:342x230x-219.4
	3 PH, 380V-480V, 47-63Hz, 32.0/40.0A		
GD200A-015G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 40.0A	3 PH, 0V-Uinput, 0-400Hz, 32.0A, 15.0 kW	
	3 PH, 380V-480V, 47-63Hz, 40.0A		
GD200A-018P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 47A	3 PH, 0V-Uinput, 0-400Hz, 38.0A, 18.5 kW	
	3 PH, 380V-480V, 47-63Hz, 47A		
GD200A-015G/018P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 40.0/47A	3 PH, 0V-Uinput, 0-400Hz, 32.0/38.0A, 15.0/18.5 kW	
	3 PH, 380V-480V, 47-63Hz, 40.0/47A		
GD200A-018G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 47A	3 PH, 0V-Uinput, 0-400Hz, 38.0A, 18.5 kW	
	3 PH, 380V-480V, 47-63Hz, 47A		
GD200A-022P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 56A	3 PH, 0V-Uinput, 0-400Hz, 45.0A, 22 kW	
	3 PH, 380V-480V, 47-63Hz, 56A		
GD200A-018G/022P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 47/56A	3 PH, 0V-Uinput, 0-400Hz, 38.0/45.0A, 18.5/22 kW	
	3 PH, 380V-480V, 47-63Hz, 47/56A		
*Remark: Uinput means Rated Input Voltage			



Product Service

Attestation of Conformity

No. N8A 072237 0098 Rev. 03

Model No.	Rated Input	Rated Output *	Size (mm)
GD350A-1R5G/2R2P-4	3PH, 380-480V, 47-63Hz, 5/5.8A	3PH, 0-Uinput, 0-400Hz, 3.7/5A, 1.5/2.2 kW	I:186 x126 x185
	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 5/5.8A		
GD350A-2R2G/003P-4	3PH, 380-480V, 47-63Hz, 5.8/11A	3PH, 0-Uinput, 0-400Hz, 5/7A, 2.2/3 kW	
	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 5.8/11A		
GD350A-004G/5R5P-4	3PH, 380-480V, 47-63Hz, 13.5/19.5A	3PH, 0-Uinput, 0-400Hz, 9.5/12.5A, 4/5.5 kW	J:186 x126 x201
	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 13.5/19.5A		
GD350A-5R5G/7R5P-4	3PH, 380-480V, 47-63Hz, 19.5/23A	3PH, 0-Uinput, 0-400Hz, 14/17A, 5.5/7.5 kW	
	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 19.5/23A		
GD350A-7R5G/011P-4	3PH, 380-480V, 47-63Hz, 25/30A	3PH, 0-Uinput, 0-400Hz, 18.5/23A, 7.5/11 kW	K:256 x146x192
	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 25/30A		
GD350A-011G/015P-4	3PH, 380-480V, 47-63Hz, 32/40A	3PH, 0-Uinput, 0-400Hz, 25/32A, 11/15 kW	L:320 x170 x220
	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 32/40A		
GD350A-015G/018P-4	3PH, 380-480V, 47-63Hz, 40/45A	3PH, 0-Uinput, 0-400Hz, 32/38A, 15/18 kW	
	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 40/45A		
* Remark: Uinput - Rated Input Voltage			