



Product Service

Attestation of Conformity

No. N8A 072237 0100 Rev. 02

Holder of Certificate: **Shenzhen INVT Electric Co., Ltd.**
INVT Guangming Technology Building, Songbai Road
Matian, Guangming District
518106 Shenzhen
PEOPLE'S REPUBLIC OF CHINA

Product: **Electronic frequency converter
(Frequency Inverter)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64105223045201

Date, 2022-06-21

(Frank Zhu)

Page 1 of 8

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 072237 0100 Rev. 02

Model(s):

GD300-022G-4, GD300-030P-4, GD300-030G-4,
 GD300-037P-4, GD300-037G-4, GD300-045P-4,
 GD300-045G-4, GD300-055P-4, GD300-055G-4,
 GD300-075P-4, GD300-075G-4, GD300-090P-4,
 GD300-090G-4, GD300-110P-4, GD300-110G-4,
 GD300-132P-4, GD200-022G-4, GD200-030P-4,
 GD200-022G/030P-4, GD200-030G-4, GD200-037P-4,
 GD200-030G/037P-4, GD200-037G-4, GD200-045P-4,
 GD200-037G/045P-4, GD200-045G-4, GD200-055P-4,
 GD200-045G/055P-4, GD200-055G-4, GD200-075P-4,
 GD200-055G/075P-4, GD200-075G-4, GD200-090P-4,
 GD200-075G/090P-4, GD200-090G-4, GD200-110P-4,
 GD200-090G/110P-4, GD200-110G-4, GD200-132P-4,
 GD200-110G/132P-4, GD200A-022G-4, GD200A-030P-4,
 GD200A-022G/030P-4, GD200A-030G-4, GD200A-037P-4,
 GD200A-030G/037P-4, GD200A-037G-4, GD200A-045P-4,
 GD200A-037G/045P-4, GD200A-045G-4, GD200A-055P-4,
 GD200A-045G/055P-4, GD200A-055G-4, GD200A-075P-4,
 GD200A-055G/075P-4, GD200A-075G-4, GD200A-090P-4,
 GD200A-075G/090P-4, GD200A-090G-4, GD200A-110P-4,
 GD200A-090G/110P-4, GD200A-110G-4, GD200A-132P-4,
 GD200A-110G/132P-4

Brand:

INVT



Page 2 of 8

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 072237 0100 Rev. 02

Parameters:

Rated input:	See below pages
Rated output:	See below pages
Installation:	BDM
Protection Class:	I
Degree of Protection:	IP 20
Rated Operating time:	Continuous
Construction:	Built-in

Remarks:

- When installing the equipment, all requirements of the mentioned standard must be fulfilled and it should be suitably installed in closed electrical operation area.
- Maximum operating temperature is 40°C.
- The input and output circuits were considered as DVC C circuits and signal circuit was considered as DVC A circuit.
- TN-S, TN-C, TN-C-S and TT (not corner earthed) power systems were evaluated.
- The frequency inverter has no overcurrent protective device. For safe operation, a suitable external circuit breaker must be employed before installation.

Tested according to:

EN 61800-5-1:2007/A11:2021

Page 3 of 8

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 072237 0100 Rev. 02

Parameters:

Model	Rated Input	Rated Output
GD300-022G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 56A	3 PH, 0V-Uinput, 0-400Hz, 45A, 22kW
	3 PH, 380V-480V, 47-63Hz, 56A	
GD300-030P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 70A	3 PH, 0V-Uinput, 0-400Hz, 60A, 30kW
	3 PH, 380V-480V, 47-63Hz, 70A	
GD300-030G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 70A	3 PH, 0V-Uinput, 0-400Hz, 60A, 30kW
	3 PH, 380V-480V, 47-63Hz, 70A	
GD300-037P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 80A	3 PH, 0V-Uinput, 0-400Hz, 75A, 37kW
	3 PH, 380V-480V, 47-63Hz, 80A	
GD300-037G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 80A	3 PH, 0V-Uinput, 0-400Hz, 75A, 37kW
	3 PH, 380V-480V, 47-63Hz, 80A	
GD300-045P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 94A	3 PH, 0V-Uinput, 0-400Hz, 92A, 45kW
	3 PH, 380V-480V, 47-63Hz, 94A	
GD300-045G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 94A	3 PH, 0V-Uinput, 0-400Hz, 92A, 45kW
	3 PH, 380V-480V, 47-63Hz, 94A	
GD300-055P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 128A	3 PH, 0V-Uinput, 0-400Hz, 115A, 55kW
	3 PH, 380V-480V, 47-63Hz, 128A	
GD300-055G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 128A	3 PH, 0V-Uinput, 0-400Hz, 115A, 55kW
	3 PH, 380V-480V, 47-63Hz, 128A	
GD300-075P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 160A	3 PH, 0V-Uinput, 0-400Hz, 150A, 75kW
	3 PH, 380V-480V, 47-63Hz, 160A	
GD300-075G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 160A	3 PH, 0V-Uinput, 0-400Hz, 150A, 75kW
	3 PH, 380V-480V, 47-63Hz, 160A	
GD300-090P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 190A	3 PH, 0V-Uinput, 0-400Hz, 180A, 90kW
	3 PH, 380V-480V, 47-63Hz, 190A	
GD300-090G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 190A	3 PH, 0V-Uinput, 0-400Hz, 180A, 90kW
	3 PH, 380V-480V, 47-63Hz, 190A	
GD300-110P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 225A	3 PH, 0V-Uinput, 0-400Hz, 215A, 110kW
	3 PH, 380V-480V, 47-63Hz, 225A	
GD300-110G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 225A	3 PH, 0V-Uinput, 0-400Hz, 215A, 110kW
	3 PH, 380V-480V, 47-63Hz, 225A	
GD300-132P-4	3 PH, 380V(-15%)-400V(+10%), 47-63Hz, 265A	3 PH, 0V-Uinput, 0-400Hz, 260A, 132kW
	3 PH, 380V-480V, 47-63Hz, 265A	



Attestation of Conformity

No. N8A 072237 0100 Rev. 02

Model	Rated Input	Rated Output
GD200-022G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 56A	3 PH, 0V-Uinput, 0-400Hz, 45A, 22kW
	3 PH, 380V-480V, 47-63Hz, 56A	
GD200-030P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,70A	3 PH, 0V-Uinput, 0-400Hz, 60A, 30kW
	3 PH, 380V-480V, 47-63Hz, 70A	
GD200-022G/030P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 56/70A	3 PH, 0V-Uinput, 0-400Hz, 45/60A, 22/30kW
	3 PH, 380V-480V, 47-63Hz, 56/70A	
GD200-030G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,70A	3 PH, 0V-Uinput, 0-400Hz, 60A, 30kW
	3 PH, 380V-480V, 47-63Hz, 70A	
GD200-037P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,80A	3 PH, 0V-Uinput, 0-400Hz, 75A, 37kW
	3 PH, 380V-480V, 47-63Hz, 80A	
GD200-030G/037P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 70/80A	3 PH, 0V-Uinput, 0-400Hz, 60/75A, 30/37kW
	3 PH, 380V-480V, 47-63Hz, 70/80A	
GD200-037G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,80A	3 PH, 0V-Uinput, 0-400Hz, 75A, 37kW
	3 PH, 380V-480V, 47-63Hz, 80A	
GD200-045P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,94A	3 PH, 0V-Uinput, 0-400Hz, 92A, 45kW
	3 PH, 380V-480V, 47-63Hz, 94A	
GD200-037G/045P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 80/94A	3 PH, 0V-Uinput, 0-400Hz, 75/92A, 37/45kW
	3 PH, 380V-480V, 47-63Hz, 80/94A	
GD200-045G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,94A	3 PH, 0V-Uinput, 0-400Hz, 92A, 45kW
	3 PH, 380V-480V, 47-63Hz, 94A	
GD200-055P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,128A	3 PH, 0V-Uinput, 0-400Hz, 115A, 55kW
	3 PH, 380V-480V, 47-63Hz, 128A	
GD200-045G/055P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 94/128A	3 PH, 0V-Uinput, 0-400Hz, 92/115A, 45/55kW
	3 PH, 380V-480V, 47-63Hz, 94/128A	
GD200-055G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,128A	3 PH, 0V-Uinput, 0-400Hz, 115A, 55kW
	3 PH, 380V-480V, 47-63Hz, 128A	
GD200-075P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,160A	3 PH, 0V-Uinput, 0-400Hz, 150A, 75kW
	3 PH, 380V-480V, 47-63Hz, 160A	
GD200-055G/075P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 128/160A	3 PH, 0V-Uinput, 0-400Hz, 115/150A, 55/75kW
	3 PH, 380V-480V, 47-63Hz, 128/160A	
GD200-075G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz,160A	3 PH, 0V-Uinput, 0-400Hz, 150A, 75kW
	3 PH, 380V-480V, 47-63Hz, 160A	

Page 5 of 8

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 072237 0100 Rev. 02

GD200-090P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 190A	3 PH, 0V-Uinput, 0-400Hz, 180A, 90kW
	3 PH, 380V-480V, 47-63Hz, 190A	
GD200-075G/090P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 160/190A	3 PH, 0V-Uinput, 0-400Hz, 150/180A, 75/90kW
	3 PH, 380V-480V, 47-63Hz, 160/190A	
GD200-090G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 190A	3 PH, 0V-Uinput, 0-400Hz, 180A, 90kW
	3 PH, 380V-480V, 47-63Hz, 190A	
GD200-110P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 225A	3 PH, 0V-Uinput, 0-400Hz, 215A, 110kW
	3 PH, 380V-480V, 47-63Hz, 225A	
GD200-090G/110P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 190/225A	3 PH, 0V-Uinput, 0-400Hz, 180/215A, 90/110kW
	3 PH, 380V-480V, 47-63Hz, 190/225A	
GD200-110G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 225A	3 PH, 0V-Uinput, 0-400Hz, 215A, 110kW
	3 PH, 380V-480V, 47-63Hz, 225A	
GD200-132P-4	3 PH, 380V(-15%)-400V(+10%), 47-63Hz, 265A	3 PH, 0V-Uinput, 0-400Hz, 260A, 132kW
	3 PH, 380V-480V, 47-63Hz, 265A	
GD200-110G/132P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 225/265A	3 PH, 0V-Uinput, 0-400Hz, 215/260A, 110/132kW
	3 PH, 380V-480V, 47-63Hz, 225/265A	

Page 6 of 8

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 072237 0100 Rev. 02

Model	Rated Input	Rated Output
GD200A-022G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 56A	3 PH, 0V-Uinput, 0-400Hz, 45A, 22kW
	3 PH, 380V-480V, 47-63Hz, 56A	
GD200A-030P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 70A	3 PH, 0V-Uinput, 0-400Hz, 60A, 30kW
	3 PH, 380V-480V, 47-63Hz, 70A	
GD200A-022G/030P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 56/70A	3 PH, 0V-Uinput, 0-400Hz, 45/60A, 22/30kW
	3 PH, 380V-480V, 47-63Hz, 56/70A	
GD200A-030G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 70A	3 PH, 0V-Uinput, 0-400Hz, 60A, 30kW
	3 PH, 380V-480V, 47-63Hz, 70A	
GD200A-037P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 80A	3 PH, 0V-Uinput, 0-400Hz, 75A, 37kW
	3 PH, 380V-480V, 47-63Hz, 80A	
GD200A-030G/037P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 70/80A	3 PH, 0V-Uinput, 0-400Hz, 60/75A, 30/37kW
	3 PH, 380V-480V, 47-63Hz, 70/80A	
GD200A-037G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 80A	3 PH, 0V-Uinput, 0-400Hz, 75A, 37kW
	3 PH, 380V-480V, 47-63Hz, 80A	
GD200A-045P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 94A	3 PH, 0V-Uinput, 0-400Hz, 92A, 45kW
	3 PH, 380V-480V, 47-63Hz, 94A	
GD200A-037G/045P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 80/94A	3 PH, 0V-Uinput, 0-400Hz, 75/92A, 37/45kW
	3 PH, 380V-480V, 47-63Hz, 80/94A	
GD200A-045G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 94A	3 PH, 0V-Uinput, 0-400Hz, 92A, 45kW
	3 PH, 380V-480V, 47-63Hz, 94A	
GD200A-055P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 128A	3 PH, 0V-Uinput, 0-400Hz, 115A, 55kW
	3 PH, 380V-480V, 47-63Hz, 128A	
GD200A-045G/055P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 94/128A	3 PH, 0V-Uinput, 0-400Hz, 92/115A, 45/55kW
	3 PH, 380V-480V, 47-63Hz, 94/128A	
GD200A-055G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 128A	3 PH, 0V-Uinput, 0-400Hz, 115A, 55kW
	3 PH, 380V-480V, 47-63Hz, 128A	
GD200A-075P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 160A	3 PH, 0V-Uinput, 0-400Hz, 150A, 75kW
	3 PH, 380V-480V, 47-63Hz, 160A	
GD200A-055G/075P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 128/160A	3 PH, 0V-Uinput, 0-400Hz, 115/150A, 55/75kW
	3 PH, 380V-480V, 47-63Hz, 128/160A	
GD200A-075G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 160A	3 PH, 0V-Uinput, 0-400Hz, 150A, 75kW
	3 PH, 380V-480V, 47-63Hz, 160A	



Product Service

Attestation of Conformity

No. N8A 072237 0100 Rev. 02

GD200A-090P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 190A	3 PH, 0V-Uinput, 0-400Hz, 180A, 90kW
	3 PH, 380V-480V, 47-63Hz, 190A	
GD200A-075G/090P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 160/190A	3 PH, 0V-Uinput, 0-400Hz, 150/180A, 75/90kW
	3 PH, 380V-480V, 47-63Hz, 160/190A	
GD200A-090G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 190A	3 PH, 0V-Uinput, 0-400Hz, 180A, 90kW
	3 PH, 380V-480V, 47-63Hz, 190A	
GD200A-110P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 225A	3 PH, 0V-Uinput, 0-400Hz, 215A, 110kW
	3 PH, 380V-480V, 47-63Hz, 225A	
GD200A-090G/110P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 190/225A	3 PH, 0V-Uinput, 0-400Hz, 180/215A, 90/110kW
	3 PH, 380V-480V, 47-63Hz, 190/225A	
GD200A-110G-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 225A	3 PH, 0V-Uinput, 0-400Hz, 215A, 110kW
	3 PH, 380V-480V, 47-63Hz, 225A	
GD200A-132P-4	3 PH, 380V(-15%)-400V(+10%), 47-63Hz, 265A	3 PH, 0V-Uinput, 0-400Hz, 260A, 132kW
	3 PH, 380V-480V, 47-63Hz, 265A	
GD200A-110G/132P-4	3 PH, 380V(-15%)-440V(+10%), 47-63Hz, 225/265A	3 PH, 0V-Uinput, 0-400Hz, 215/260A, 110/132kW
	3 PH, 380V-480V, 47-63Hz, 225/265A	

Page 8 of 8

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.