

Attestation of Conformity

No. N8AUK 072237 0127 Rev. 00

Holder of Certificate: **Shenzhen INVT Electric Co., Ltd.**
INVT Guangming Technology Building, Songbai Road
Matian, Guangming District
518106 Shenzhen
PEOPLE'S REPUBLIC OF CHINA

Product: **Electronic frequency converter
(Frequency Inverter)**

This Attestation of Conformity is issued on a voluntary basis according to the Electrical Equipment (Safety) Regulations 2016 relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the regulations and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see:
www.tuvsud.com/ps-cert

Test report no.: 64105203041404

Date, 2022-06-20



(Frank Zhu)

Page 1 of 7

After preparation of the necessary UK regulation technical documentation as well as the UK declaration of conformity the required UKCA marking can be affixed on the product. Other applicable UK regulations have to be observed.

Attestation of Conformity

No. N8AUK 072237 0127 Rev. 00

Model(s):

GD20-0R4G-S2, GD20-0R7G-S2, GD20-1R5G-S2,
GD20-2R2G-S2, GD20-0R4G-2, GD20-0R7G-2,
GD20-0R7G-4, GD20-1R5G-4, GD20-2R2G-4,
GD20-1R5G-2, GD20-2R2G-2, GD20-004G-2,
GD20-004G-4, GD20-5R5G-4, GD20-5R5G-2,
GD20-7R5G-4, GD20-7R5G-2, GD20-011G-4,
GD20-015G-4, GD20-018G-4, GD20-022G-4,
GD20-030G-4, GD20-037G-4, GD20-045G-4,
GD20-045G-4-B, GD20-055G-4, GD20-055G-4-B,
GD20-075G-4, GD20-075G-4-B, GD20-090G-4,
GD20-090G-4-B, GD20-110G-4, GD20-110G-4-B,
GD20-0R4G-S2-EU, GD20-0R7G-S2-EU,
GD20-1R5G-S2-EU, GD20-2R2G-S2-EU,
GD20-0R4G-2-EU, GD20-0R7G-2-EU, GD20-0R7G-4-EU,
GD20-1R5G-4-EU, GD20-2R2G-4-EU, GD20-1R5G-2-EU,
GD20-2R2G-2-EU, GD20-004G-2-EU, GD20-004G-4-EU,
GD20-5R5G-4-EU, GD20-5R5G-2-EU, GD20-7R5G-4-EU,
GD20-7R5G-2-EU, GD20-011G-4-EU, GD20-015G-4-EU,
GD20-018G-4-EU, GD20-022G-4-EU, GD20-030G-4-EU,
GD20-037G-4-EU, GD20-045G-4-EU, GD20-045G-4-B-EU,
GD20-055G-4-EU, GD20-055G-4-B-EU, GD20-075G-4-EU,
GD20-075G-4-B-EU, GD20-090G-4-EU,
GD20-090G-4-B-EU, GD20-110G-4-EU,
GD20-110G-4-B-EU, GD350A-018G/022P-4,
GD350A-022G/030P-4, GD350A-030G/037P-4,
GD350A-037G/045P-4, GD350A-045G/055P-4,
GD350A-055G/075P-4, GD350A-075G/090P-4,
GD350A-090G/110P-4, GD350A-110G/132P-4

Brand:

INVT



Page 2 of 7

After preparation of the necessary UK regulation technical documentation as well as the UK declaration of conformity the required UKCA marking can be affixed on the product. Other applicable UK regulations have to be observed.

Attestation of Conformity

No. N8AUK 072237 0127 Rev. 00

Parameters:

Rated input:	see below pages
Rated output:	see below pages
Installation:	BDM
Protection Class:	I
Construction:	Built-in

Remark:

- When installing the equipment, all requirements of the mentioned standard must be fulfilled and it should be suitably installed in closed electrical operation area, and fire/mechanical protection enclosure shall be provided.
- The maximum operating temperature is 40°C
- The input and output circuits were considered as DVC C circuits and signal circuit was considered as DVC A circuit.
- TN-S, TN-C, TN-C-S, TT (not corner earthed) power systems were evaluated.
- The equipment has no overcurrent protective device. For safety operation, a suitable external circuit breaker must be employed before installation.

Tested according to:

EN 61800-5-1:2007/A11:2021

Attestation of Conformity

No. N8AUK 072237 0127 Rev. 00

Parameters:

Model No.	Rated Input	Rated Output*	Frame Size (mm)		
GD20-0R4G-S2 GD20-0R4G-S2-EU	1PH, 220V(-15%)-240V(+10%), 47-63Hz, 6.5A	3PH, 0V-Uinput, 0-400Hz, 2.5A, 0.4 kW	Size A: 80 x 160 x 123.5		
	1PH, 200V-240V,47-63Hz, 6.5A				
GD20-0R7G-S2 GD20-0R7G-S2-EU	1PH, 220V(-15%)-240V(+10%), 47-63Hz, 9.3A	3PH, 0V-Uinput, 0-400Hz, 4.2A, 0.75 kW			
	1PH, 200V-240V,47-63Hz, 9.3A				
GD20-1R5G-S2 GD20-1R5G-S2-EU	1PH, 220V(-15%)-240V(+10%), 47-63Hz, 15.7A	3PH, 0V-Uinput, 0-400Hz, 7.5A, 1.5 kW		Size B: 80 x 185 x 140.5	
	1PH, 200V-240V,47-63Hz, 15.7A				
GD20-2R2G-S2 GD20-2R2G-S2-EU	1PH, 220V(-15%)-240V(+10%), 47-63Hz, 24.0A	3PH, 0V-Uinput, 0-400Hz, 10.0A, 2.2 kW			
	1PH, 200V-240V,47-63Hz, 24.0A				
GD20-0R4G-2 GD20-0R4G-2-EU	3PH, 220V(-15%)-240V(+10%), 47-63Hz, 3.7A	3PH, 0V-Uinput, 0-400Hz, 2.5A, 0.4 kW			Size C: 80 x 185 x 140.5
	3PH, 200V-240V,47-63Hz, 3.7A				
GD20-0R7G-2 GD20-0R7G-2-EU	3PH, 220V(-15%)-240V(+10%), 47-63Hz, 5.0A	3PH, 0V-Uinput, 0-400Hz, 4.2A, 0.75 kW			
	3PH, 200V-240V,47-63Hz, 5.0A				
GD20-0R7G-4 GD20-0R7G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 3.4A	3PH, 0V-Uinput, 0-400Hz, 2.5A, 0.75 kW			
	3PH, 380V-480V,47-63Hz, 3.4A				
GD20-1R5G-4 GD20-1R5G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 5.0A	3PH, 0V-Uinput, 0-400Hz, 4.2A, 1.5 kW			
	3PH, 380V-480V,47-63Hz, 5.0A				
GD20-2R2G-4 GD20-2R2G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 5.8A	3PH, 0V-Uinput, 0-400Hz, 5.5A, 2.2 kW			
	3PH, 380V-480V,47-63Hz, 5.8A				
GD20-1R5G-2 GD20-1R5G-2-EU	3PH, 220V(-15%)-240V(+10%), 47-63Hz, 7.7A	3PH, 0V-Uinput, 0-400Hz, 7.5A, 1.5 kW	Size D: 146 x 256 x 167		
	3PH, 200V-240V,47-63Hz, 7.7A				
GD20-2R2G-2 GD20-2R2G-2-EU	3PH, 220V(-15%)-240V(+10%), 47-63Hz, 11.0A	3PH, 0V-Uinput, 0-400Hz, 10.0A, 2.2 kW			
	3PH, 200V-240V,47-63Hz, 11.0A				
GD20-004G-2 GD20-004G-2-EU	3PH, 220V(-15%)-240V(+10%), 47-63Hz, 17.0A	3PH, 0V-Uinput, 0-400Hz, 16.0A, 4.0 kW			
	3PH, 200V-240V,47-63Hz, 17.0A				

Attestation of Conformity

No. N8AUK 072237 0127 Rev. 00

GD20-004G-4 GD20-004G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 13.5A	3PH, 0V-Uinput, 0-400Hz, 9.5A, 4.0 kW	Size E: 170 x 320 x 196.3	
	3PH, 380V-480V,47-63Hz, 13.5A			
GD20-5R5G-4 GD20-5R5G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 19.5A	3PH, 0V-Uinput, 0-400Hz, 14.0A, 5.5 kW		
	3PH, 380V-480V, 47-63Hz, 19.5A			
GD20-5R5G-2 GD20-5R5G-2-EU	3PH, 220V(-15%)-240V(+10%), 47-63Hz, 21.0A	3PH, 0V-Uinput, 0-400Hz, 20.0A, 5.5 kW		
	3PH, 200V-240V,47-63Hz, 21.0A			
GD20-7R5G-2 GD20-7R5G-2-EU	3PH, 220V(-15%)-240V(+10%), 47-63Hz, 31.0A	3PH, 0V-Uinput, 0-400Hz, 30.0A, 7.5 kW		
	3PH, 200V-240V,47-63Hz, 31.0A			
GD20-7R5G-4 GD20-7R5G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 25.0A	3PH, 0V-Uinput, 0-400Hz, 18.5A, 7.5 kW		
	3PH, 380V-480V, 47-63Hz, 25.0A			
GD20-011G-4 GD20-011G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 32.0A	3PH, 0V-Uinput, 0-400Hz, 25.0A, 11.0 kW		
	3PH, 380V-480V, 47-63Hz, 32.0A			
GD20-015G-4 GD20-015G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 40.0A	3PH, 0V-Uinput, 0-400Hz, 32.0A, 15.0 kW		
	3PH, 380V-480V, 47-63Hz, 40.0A			
GD20-018G-4 GD20-018G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 47.0A	3PH, 0V-Uinput, 0-400Hz, 38.0A, 18.5 kW		Size F: 200 x 340.6 x 184.3
	3PH, 380V-480V, 47-63Hz, 47.0A			
GD20-022G-4 GD20-022G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 51.0A	3PH, 0V-Uinput, 0-400Hz, 45.0A, 22.0 kW		
	3PH, 380V-480V, 47-63Hz, 51.0A			
GD20-030G-4 GD20-030G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 70.0A	3PH, 0V-Uinput, 0-400Hz, 60.0A, 30.0 kW		
	3PH, 380V-480V, 47-63Hz, 70.0A			
GD20-037G-4 GD20-037G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 80.0A	3PH, 0V-Uinput, 0-400Hz, 75.0A, 37.0 kW	Size G: 250 x 400 x 202	
	3PH, 380V-480V, 47-63Hz, 80.0A			
GD20-045G-4 GD20-045G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 98.0A	3PH, 0V-Uinput, 0-400Hz, 92.0A, 45.0 kW	Size H: 282 x 560 x 238	
	3PH, 380V-480V, 47-63Hz, 98.0A			
GD20-045G-4-B GD20-045G-4-B-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 98.0A	3PH, 0V-Uinput, 0-400Hz, 92.0A, 45.0 kW		
	3PH, 380V-480V, 47-63Hz, 98.0A			

Page 5 of 7

After preparation of the necessary UK regulation technical documentation as well as the UK declaration of conformity the required UKCA marking can be affixed on the product. Other applicable UK regulations have to be observed.

Attestation of Conformity

No. N8AUK 072237 0127 Rev. 00

GD20-055G-4 GD20-055G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 128.0A	3PH, 0V-Uinput, 0-400Hz, 115.0A, 55.0 kW	Size I: 338 x 554 x 329.2
	3PH, 380V-480V, 47-63Hz, 128.0A		
GD20-055G-4-B GD20-055G-4-B-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 128.0A	3PH, 0V-Uinput, 0-400Hz, 115.0A, 55.0 kW	
	3PH, 380V-480V, 47-63Hz, 128.0A		
GD20-075G-4 GD20-075G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 139.0A	3PH, 0V-Uinput, 0-400Hz, 150.0A, 75.0 kW	
	3PH, 380V-480V, 47-63Hz, 139.0A		
GD20-075G-4-B GD20-075G-4-B-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 139.0A	3PH, 0V-Uinput, 0-400Hz, 150.0A, 75.0 kW	
	3PH, 380V-480V, 47-63Hz, 139.0A		
GD20-090G-4 GD20-090G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 168.0A	3PH, 0V-Uinput, 0-400Hz, 180.0A, 90.0 kW	
	3PH, 380V-480V, 47-63Hz, 168.0A		
GD20-090G-4-B GD20-090G-4-B-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 168.0A	3PH, 0V-Uinput, 0-400Hz, 180.0A, 90.0 kW	
	3PH, 380V-480V, 47-63Hz, 168.0A		
GD20-110G-4 GD20-110G-4-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 201.0A	3PH, 0V-Uinput, 0-400Hz, 215.0A, 110.0 kW	
	3PH, 380V-480V, 47-63Hz, 201.0A		
GD20-110G-4-B GD20-110G-4-B-EU	3PH, 380V(-15%)-440V(+10%), 47-63Hz, 201.0A	3PH, 0V-Uinput, 0-400Hz, 215.0A, 110.0 kW	
	3PH, 380V-480V, 47-63Hz, 201.0A		

Attestation of Conformity

No. N8AUK 072237 0127 Rev. 00

Model No.	Rated Input	Rated Output *	Frame Size (mm)
GD350A-018G/022P-4	3PH, 380-480V, 47-63Hz, 45/51A	3PH, 0-Uinput, 0-400Hz, 38/45A, 18.5/22 kW	Size F: 371 x 266 x 208
	3PH, 380V(-15%)-440V(+10%), 47-63Hz,45/51A		
GD350A-022G/030P-4	3PH, 380-480V, 47-63Hz, 51/64A	3PH, 0-Uinput, 0-400Hz, 45/60A, 22/30 kW	Size G: 430 x 316 x 223
	3PH, 380V(-15%)-440V(+10%), 47-63Hz,51/64A		
GD350A-030G/037P-4	3PH, 380-480V, 47-63Hz,64/80A	3PH, 0-Uinput, 0-400Hz, 60/75A, 30/37 kW	Size H: 580 x 352 x 258
	3PH, 380V(-15%)-440V(+10%), 47-63Hz,64/80A		
GD350A-037G/045P-4	3PH, 380-480V, 47-63Hz,80/98A	3PH, 0-Uinput, 0-400Hz, 75/92A, 37/45 kW	Size I: 600 x 418.5 x 330
	3PH, 380V(-15%)-440V(+10%), 47-63Hz,80/98A		
GD350A-045G/055P-4	3PH, 380-480V, 47-63Hz,98/128A	3PH, 0-Uinput, 0-400Hz, 92/115A, 45/55 kW	Size I: 600 x 418.5 x 330
	3PH, 380V(-15%)-440V(+10%), 47-63Hz,98/128A		
GD350A-055G/075P-4	3PH, 380-480V, 47-63Hz,128/139A	3PH, 0-Uinput, 0-400Hz, 115/150A, 55/75 kW	Size I: 600 x 418.5 x 330
	3PH, 380V(-15%)-440V(+10%), 47-63Hz,128/139A		
GD350A-075G/090P-4	3PH, 380-480V, 47-63Hz,139/168A	3PH, 0-Uinput, 0-400Hz, 150/170A, 75/90 kW	Size I: 600 x 418.5 x 330
	3PH, 380V(-15%)-440V(+10%), 47-63Hz,139/168A		
GD350A-090G/110P-4	3PH, 380-480V, 47-63Hz,168/201A	3PH, 0-Uinput, 0-400Hz, 180/215A, 90/110 kW	Size I: 600 x 418.5 x 330
	3PH, 380V(-15%)-440V(+10%), 47-63Hz,168/201A		
GD350A-110G/132P-4	3PH, 380-480V, 47-63Hz,201/265A	3PH, 0-Uinput, 0-400Hz, 215/260A, 110/132 kW	Size I: 600 x 418.5 x 330
	3PH, 380V(-15%)-440V(+10%), 47-63Hz,201/265A		
* Remark: Uinput - Rated Input Voltage			